

# Material Safety Data Sheet

Complies with OSHA Communication Standard

29 CFR 1910.1200

**Product Name on Label** ***BD-Zorb***

## I. Supplier's Information

Duda Diesel LLC, 7055A Greenbrier Rd, Madison, AL 35756

Phone: 256-417-4337 Fax: 866-568-3412

### Manufacturers Hazard Rating

Toxicity – 1	Fire – 2	Reactivity – 0	Special – 0	
Hazard Rating Scale				
Extreme=4	High=3	Moderate=2	Slight=1	Insignificant=0

## I. Ingredients and Identity Information

Components	%	OSHA		ACGIH TLV	
		PEL	STEL	TLV	TLV STEL
Hardwood Wood Dust	88	15 mgmg/m <sup>3</sup> total dust <hr/> 5mg/m <sup>3</sup> respirabe fraction as a nuisance dust	6 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA	N/A
Sulfonated styrene- divinylbenzene copolymer	11-12	N/A	N/A	N/A	N/A
Water	<1	N/A	N/A	N/A	N/A

## II. Physical/Chemical Characteristics

Appearance and odor	Tan particles with amber to black spherical beads with no odor		
Melting point	N/A	Vapor pressure (mm/Hg)	N/A
Vapor Density	N/A	Evaporation Rate	N/A
Melting point	N/A	Vapor pressure (mm/Hg)	N/A

## III. Fire and Explosion Hazard Data

NFPA Fire Hazard Class	1	Flash Point (Deg. C)	N/A
Auto Ignition Temperature (Deg. F)	400 to 500		
Flammable Limits	Lower 40.0 m/m <sup>3</sup>	Conditions of Flammability	Concentrated dust clouds
Extinguishing Media	Water Fog		

Special Fire Fighting Procedures	Wear MSHA/NIOSH approved, pressure demand, self contained breathing apparatus
Unusual Fire and Explosion Hazards	Wood dusts may form explosive mixtures with air in the presence of an ignition source

## IV. Reactivity Data

NFPA Reactivity Rating	1		
Conditions to avoid	Temperatures above 300 degrees F		
Stability	Stable	Hazardous Polymerization	None
Extinguishing Media	CO2, Dry Chemical, Water Fog		
Incompatibility	Avoid strong oxidizing agents and concentrated nitric acid		
Hazardous decomposition by-products	Styrene monomer, divinylbenzene, CO, CO2, SO2 and SO3		

## V. Health Hazard Data

NFPA Health Hazard	1	Exposure Limits	ND	Mutagenicity	ND
Carcinogenicity	ND	Reproductive Toxicity	ND	Teratogenicity	ND
Irritancy of Product	Eyes and Skin		OSHA Regulated?	N/A	
Effect of acute exposure	Can produce mechanical irritation of eyes				
Emergency and First Aid Procedures	Flush eyes and skin with copious quantities of water for 15 minutes. If irritation persists, see a physician				

## VI. Precautions for Safe Handling and Use

Precautions in case of spill or release	Product will cause a slip hazard on hard surfaces. Sweep up immediately for re-use or disposal
Precautions for handling and storage	Keep containers sealed to avoid exposure to humidity and water. Expansion of product could cause containers to burst. Store in cool dry area (above 32 degrees F and below 120 degrees F).
Special Precautions for handling and storage	Avoid contact with Nitric acid and strong oxidizing agents.
Waste Disposal method	As supplied, new and used product is not considered as hazardous waste. However, during use material may absorb methanol, glycerin and methyl ester. Do not compost the spent material due to the possibility of auto-ignition.

## VII. Control Measures

Personal Protective Equipment	Wear impervious gloves and splash goggles when handling
Other Protective Clothing or Equipment	Wear trousers and long sleeve shirts to avoid skin exposure.
Work and Hygienic Practices	Flush product from hands with soapy water. Clean up all spilled product immediately to avoid slip hazards
Precautions during application of product	Provide adequate ventilation to avoid concentrations of dust. Concentrated dust can cause explosion.

## VIII. Regulatory Information and References

Section 302 Reporting if above	None
Section 304 Reporting if above	None
Section 313 Reporting required	No
CERCLA reporting required if above	None
RCRA reporting required	No
Canadian WHMIS Classification	Other
D.O.T. Hazard Name	Not required by D.O.T.
D.O.T. ID Number	N/A
D.O.T. Hazard Class	N/A

The data and recommendations presented are based on our research and the research of others, and are believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Duda Diesel LLC assumes no responsibility for the injury to customers or third persons caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, since actual use by others is beyond our control, no guarantee, expressed or implied is made by Duda Diesel LLC as to the effects of such use, the results to be obtained, or the safety and toxicity of the product. Duda Diesel LLC assumes no liability arising out of the use, or misuse, by others, of the product referred to herein. Information provided herein is provided by Duda Diesel LLC solely for the customer's assistance in complying with the Occupational Safety and Health Act of 1970 and regulations hereunder. Any other use is prohibited.