

30-50 WHITE™



30-50 WHITE™ is a dry ground marble with a very coarse particle size that is controlled between 30 and 50 mesh screens. 30-50 White is NSF listed for water treatment and used in applications such as:

- Textured Coatings & Stuccos based on Cement or Acrylics
- Water Filtration System (NSF listed)*
- Acid Neutralization

TYPICAL PROPERTIES

Source	Marble Hill, GA
CaCO ₃ (wt.%)	94
Acid Insolubles (wt. %)	2
Moisture (wt. %)	0.15
Plus 30 Mesh (wt. %)	1.0
Minus 50 Mesh (wt. %)	10
Hardness (µm)	3
Refractive Index, mean	1.6
Specific Gravity	2.7
Solid Density (lb/gal)	22.7
Bulk Density: (lb/ft ³)	
- Loose	90
- Packed	105

DAT001FGCC1
 July 2012
 ©IMERY'S 2012
 Sixth Edition
 All products are registered
 trademarks of IMERY'S

CAS No. 1317-65-3

IMERY'S
 100 Mansell Court East
 Suite 300
 Roswell, GA 30076

General:
 Tel: (770) 594.0660
 Fax: (770) 645.3384
www.imerys-perfmins.com

Customer Service:
 Tel: (888) 277.9636
 Fax: (770) 645.3631

IMERY'S is a business name of
 IMERY'S Pigments, Inc.,
 IMERY'S Kaolin, Inc. and
 IMERY'S Marble, Inc.
 Registered in the USA.

This information is
 believed to be correct.
 However, this information
 does not constitute any r
 epresentation, condition or
 warranty, nor do
 we guarantee results
 to be obtained. All
 recommendations and
 sales are made on the condition
 that we will not be held liable for
 any damages resulting from their
 use. This provision may
 not be changed by any
 of our representatives.

