| SEBTIFICATIO | | CERTIFIED SOLAR COLLECTOR | |
|------------------|--|---------------------------|--------------------|
| S ATTA C | SUPPLIER: | BRAND: | Duda Solar |
| | Duda Energy | MODEL: | SC5825 |
| | 7055A Greenbrier Rd Madison, AL 35756 USA | COLLECTOR TYPE: | Tubular |
| | In Accordance with: | CERTIFICATION #: | 10001879 |
| ESTABLISHED 1980 | SRCC Standard 100-2010-08 | Original Certification: | September 19, 2013 |

The solar collector listed below has been evaluated by the Solar Rating & Certification Corporation™ (SRCC™), an ANSI accredited and EPA recognized Certification Body, in accordance with SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC. This award of certification is subject to all terms and conditions of the Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

Expiration Date:

July 13, 2023

| | COLLECTOR THERMAL PERFORMANCE RATING | | | | | | | | | | | | |
|---------------------|--------------------------------------|---|-----|------------------------------------|---------------------------------------|--------------------|--------------------|--|--|--|--|--|--|
| | Kilowatt-hours (th | ermal) Per Panel Per [| Day | Thousands of Btu Per Panel Per Day | | | | | | | | | |
| Climate -> | High Radiation | Medium Radiation (4.7 kWh/m².day) Low Radiation (3.1 kWh/m².day) Climate -> Category (Ti-Ta) High Radiation (2000 Btu/ft².day) | | , v | Medium Radiation | Low Radiation | | | | | | | |
| Category (Ti-Ta) | (6.3 kWh/m².day) | | | | (2000 Btu/ft².day) | (1500 Btu/ft².day) | (1000 Btu/ft².day) | | | | | | |
| A (-5 °C) | 11.1 | 8.4 | 5.6 | A (-9 °F) | 38.0 | 28.6 | 19.3 | | | | | | |
| B (5 °C) | 10.8 | 8.1 | 5.4 | B (9 °F) | 37.0 | 27.7 | 18.3 | | | | | | |
| C (20 °C) | 10.4 | 7.7 | 4.9 | C (36 °F) | 35.4 | 26.1 | 16.8 | | | | | | |
| D (50 °C) | 9.3 | 6.6 | 3.9 | D (90 °F) | 31.7 | 22.4 | 13.3 | | | | | | |
| E (80 °C) | 8.2 | 5.5 | 2.8 | E (144 °F) | 27.8 | 18.7 | 9.6 | | | | | | |
| | | | | | • • • • • • • • • • • • • • • • • • • | 011 1 1 | | | | | | | |

A- Pool Heating (Warm Climate) B- Pool Heating (Cool Climate) C- Water Heating (Warm Climate) D- Space & Water Heating (Cool Climate) E- Commercial Hot Water & Cooling

| COLLECTOR SPECIFICATIONS | | | | | | | | | | |
|--------------------------|----------------------|-----------------------|-------------------|-----------|---------|--|--|--|--|--|
| Gross Area: | 3.824 m ² | 41.16 ft ² | Dry Weight: 80 kg | | 176 lb | | | | | |
| Net Aperture Area: | 2.361 m ² | 25.41 ft ² | Fluid Capacity: | 1.5 liter | 0.4 gal | | | | | |
| Absorber Area: | 2.032 m ² | 21.87 ft ² | Test Pressure: | 900 kPa | 131 psi | | | | | |

| TECHNICAL INFO | RMATION | Tested in accorda | Tested in accordance with: ISO 9806 | | | | |
|---|---|-------------------|-------------------------------------|--------|-----------------------------------|--|--|
| ISO Efficiency Equation [NOTE: Based on gross area and (P)=Ti-Ta] | | | | | | | |
| SI UNITS: | η= 0.420 - 0.65440(P/G) - 0.00310(P²/G) | Y Intercept: | 0.420 | Slope: | -0.786 W/m².°C | | |
| IP UNITS: | η= 0.420 - 0.11533(P/G) - 0.00030(P²/G) | Y Intercept: | 0.420 | Slope: | -0.139 Btu/hr.ft ² .°F | | |

| Transverse Incident Angle Modifier | | | | | | Longitudinal Incident Angle Modifier at t | 0.90 | | | |
|------------------------------------|------|------|------|------|------|---|------|----------------------|-------------------------------|------------------|
| θ | 10 | 20 | 30 | 40 | 50 | 60 | 70 | Test Fluid: Water | | |
| Κτα | 1.02 | 1.06 | 1.14 | 1.25 | 1.40 | 1.55 | 1.35 | Test Mass Flow Rate: | 0.0118 kg/(s m ²) | 8.67 lb/(hr ft²) |

REMARKS:

Technical Director



Print Date: December, 2013 Page 1 of 3

© Solar Rating & Certification Corporation™ www.solar-rating.org ♦ 400 High Point Drive, Suite 400 ♦ Coccoa, Florida 32926 ♦ (321) 213-6037 ♦ Fax (321) 821-0910



SUPPLIER: **Duda Energy** 7055A Greenbrier Rd Madison, AL 35756 USA

In Accordance with: SRCC Standard 100-2010-08

CERTIFIED SOLAR COLLECTOR

| BRAND: | Duda Solar |
|-------------------------|--------------------|
| MODEL: | SC5825 |
| COLLECTOR TYPE: | Tubular |
| CERTIFICATION #: | 10001879 |
| Original Certification: | September 19, 2013 |
| Expiration Date: | July 13, 2023 |

The solar collector listed below has been evaluated by the Solar Rating & Certification Corporation[™] (SRCC[™]), an ANSI accredited and EPA recognized Certification Body, in accordance with SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC. This award of certification is subject to all terms and conditions of the Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

| ADDITIONAL INFORMATION (click here to return to the rating page) | | | | | | | | | |
|--|---|----------------|---------------|--|--|--|--|--|--|
| Test Lab: | IZES gGmbH (Institut für ZukunftsEnergieSysteme) | Test Date: | July 13, 2011 | | | | | | |
| Test Report Number: | KT_SRCC10_18 | Test Location: | outdoors | | | | | | |

| SOLAR COLLECTOR CONSTRUCTION DETAILS | | | | | | | | | | | |
|--|---|--|--|--|--|--|--|--|--|--|--|
| Header Enclosure: | | | | | | | | | | | |
| Gross Length: | Gross Length: 1.976 m Gross Width: 1.935 m Gross Depth: 0.117 m | | | | | | | | | | |
| Tube Bank: | Tube Bank: | | | | | | | | | | |
| Gross Length: 0.185 m Gross Width: 1.935 m | | | | | | | | | | | |

| COLLECTOR MATERIALS | | | | | | | | | | | |
|-----------------------------|--------------------|-------------|------------------------|----------------------|-------------|------------|---------|--|--|--|--|
| Outer Cover: Glass Tube | | Tube | Enclosure back: | Aluminum Back Insula | | ation: | Vacuum, | | | | |
| Inner Cover: | Glass | Tube | Enclosure side: | Aluminum | Side Insula | tion: | , | | | | |
| Absorber Description: | | Glass Tubes | Flow Pattern: | | | Mixed | | | | | |
| Riser Tube: | Riser Tube: Copper | | Fin: | | Glass | | | | | | |
| Absorber Coating: Selective | | Selective | Tube to fin connection | | | Mechanical | | | | | |

| GLAZING | Outer Cover | Inner Cover |
|--|-------------------------------------|-----------------|
| Material: | Glass Tube | Glass Tube |
| Surface Characteristics: | Smooth | Smooth |
| Thickness: | 1.8 mm | |
| Transmissivity: | High (equal to or greater than 90%) | Low (below 87%) |
| Gross Tube Length (uninstalled): | 1.800 m | |
| Diameter: | 0.058 m | 0.047 m |
| Tube Glazing to Header Enclosure Seal: | Silicon | e bead |
| Reflector Shape: | Reflector Material: | |

ABSORBER



Print Date: December, 2013 Page 2 of 3 © Solar Rating & Certification Corporation™

www.solar-rating.org ♦ 400 High Point Drive, Suite 400 ♦ Cocoa, Florida 32926 ♦ (321) 213-6037 ♦ Fax (321) 821-0910



Certification #: Supplier: Brand Name: Model Number:

10001879 Duda Energy Duda Solar SC5825

| Header Material: | Copper | Header OD: | 22.0 mm Header Wall: | | 2.0 mm |
|---------------------------|--------|---------------------------------------|---------------------------------------|-------------------------------|---------|
| Riser Tube Material: | Copper | Riser Tube OD: | 8.0 mm | Riser Tube Wall Thickness: | 0.4 mm |
| Fin Material: | Glass | Fin Thickness: | 0.15 mm | | |
| Flow Pattern: | Mixed | Number of Flow Tubes / Heat Pipes: | 25 Tube / Heat Pipe 75 Spacing: 75 | | 75.0 mm |
| Number of absorber tubes: | 1 | Flow Tube to Fin Bond: | Mechanical Length of Flow Path: | | |
| Length of Flow Path: | | Riser to Fin/Plate Bond: | Mechanical | | |

| INSULATION: | | | | | | | | | | | |
|---------------------------------|--------|-----------|-----------|----------------------|----|----------|-----------|--|--|--|--|
| Location | Туре | | Thickness | Location | Ту | pe | Thickness | | | | |
| Back – Top Layer: | Vacuum | | 3.7 mm | Sides – Inner Layer: | | | | | | | |
| Back – Bottom Layer: | | - | | Sides – Outer Layer: | | - | | | | | |
| Enclosure Fastening Methods: Me | | Mechanica | l Forming | Header Enclosure: | | Aluminum | | | | | |

Power Output per Collector(W)

| [Ti-Ta, G = 1000 W/m ²] | | | | | | |
|--------------------------------------|------|------|------|------|--|--|
| 0 | 10 | 30 | 50 | 70 | | |
| 1604 | 1578 | 1518 | 1449 | 1371 | | |
| | | | | | | |

PRESSURE DROP

| FRESSURE DROP | | | | | | |
|---------------|----|--|------|--------|--|--|
| Flow | ΔΡ | | Flow | ΔΡ | | |
| ml/s | Pa | | gpm | in H₂0 | | |
| 20 | 0 | | 0.32 | 0.0 | | |
| 50 | 0 | | 0.79 | 0.0 | | |
| 80 | 0 | | 1.27 | 0.0 | | |



Print Date: December, 2013 Page 3 of 3 © Solar Rating & Certification Corporation ™ www.solar-rating.org ♦ 400 High Point Drive, Suite 400 ♦ Cocoa, Florida 32926 ♦ (321) 213-6037 ♦ Fax (321) 821-0910